



Bearing Protection Ring™ - *Split Ring* Patented Technology



All dimensions in mm

Catalog Number	Min. shaft diameter	Max. shaft diameter	Outside diameter	Thickness
----------------	---------------------	---------------------	------------------	-----------

Catalog Number	Min. shaft diameter	Max. shaft diameter	Outside diameter	Thickness
----------------	---------------------	---------------------	------------------	-----------

SGR-6.9-2A4	7.9	9.0	40.6	7.1
SGR-8.0-2A4	9.1	10.0	40.6	7.1
SGR-9.0-2A4	10.1	11.0	40.6	7.1
SGR-10.1-2A4	11.1	12.2	40.6	7.1
SGR-11.2-2A4	12.3	13.2	40.6	7.1
SGR-12.2-2A4	13.3	14.2	40.6	7.1
SGR-13.2-2A4	14.3	15.4	40.6	7.1
SGR-14.4-2A4	15.5	16.4	40.6	7.1
SGR-15.4-2A4	16.5	17.4	53.3	7.1
SGR-16.4-2A4	17.5	18.5	53.3	7.1
SGR-17.6-2A4	18.6	19.7	53.3	7.1
SGR-18.7-2A4	19.8	20.7	53.3	7.1
SGR-19.7-2A4	20.8	21.7	53.3	7.1
SGR-20.7-2A4	21.8	22.7	53.3	7.1
SGR-21.7-2A4	22.8	23.7	53.3	7.1
SGR-22.8-2A4	23.8	24.9	53.3	7.1
SGR-23.9-2A4	25.0	25.9	53.3	7.1
SGR-24.9-2A4	26.0	26.9	53.3	7.1
SGR-25.9-2A4	27.0	28.1	53.3	7.1
SGR-27.1-2A4	28.2	29.1	53.3	7.1
SGR-28.1-2A4	29.2	30.1	53.3	7.1
SGR-29.1-2A4	30.2	31.2	53.3	7.1
SGR-30.3-2A4	31.3	32.3	53.3	7.1
SGR-31.3-2A4	32.4	33.3	53.3	7.1
SGR-32.3-2A4	33.4	34.4	53.3	7.1
SGR-33.4-2A4	34.5	35.4	53.3	7.1
SGR-34.4-2A4	35.5	36.4	68.1	6.6
SGR-35.5-2A4	36.5	37.6	68.1	6.6
SGR-36.6-2A4	37.7	38.6	68.1	6.6
SGR-37.6-2A4	38.7	39.6	68.1	6.6
SGR-38.6-2A4	39.7	40.8	68.1	6.6
SGR-39.8-2A4	40.9	41.8	68.1	6.6
SGR-40.8-2A4	41.9	42.8	68.1	6.6
SGR-41.8-2A4	42.9	43.9	68.1	6.6
SGR-43.0-2A4	44.0	45.0	68.1	6.6
SGR-44.0-2A4	45.1	46.0	68.1	6.6
SGR-45.0-2A4	46.1	47.1	68.1	6.6
SGR-46.1-2A4	47.2	48.1	68.1	6.6
SGR-47.1-2A4	48.2	49.1	68.1	6.6
SGR-48.2-2A4	49.2	50.3	68.1	6.6
SGR-49.3-2A4	50.4	51.3	68.1	6.6
SGR-50.3-2A4	51.4	52.3	78.7	7.1
SGR-51.3-2A4	52.4	53.5	78.7	7.1
SGR-52.5-2A4	53.6	54.5	78.7	7.1
SGR-53.5-2A4	54.6	55.5	78.7	7.1
SGR-54.5-2A4	55.6	56.6	78.7	7.1
SGR-55.7-2A4	56.7	57.7	78.7	7.1
SGR-56.7-2A4	57.8	58.7	78.7	7.1
SGR-57.7-2A4	58.8	59.8	78.7	7.1
SGR-58.8-2A4	59.9	60.8	78.7	7.1
SGR-59.8-2A4	60.9	61.8	91.4	7.1
SGR-60.9-2A4	61.9	63.0	91.4	7.1
SGR-62.0-2A4	63.1	64.0	91.4	7.1
SGR-63.0-2A4	64.1	65.0	91.4	7.1
SGR-64.0-2A4	65.1	66.2	91.4	7.1
SGR-65.2-2A4	66.3	67.2	91.4	7.1
SGR-66.2-2A4	67.3	68.2	91.4	7.1
SGR-67.2-2A4	68.3	69.3	91.4	7.1
SGR-68.4-2A4	69.4	70.4	91.4	7.1
SGR-69.4-2A4	70.5	71.4	91.4	7.1
SGR-70.4-2A4	71.5	72.5	91.4	7.1
SGR-71.5-2A4	72.6	73.5	91.4	7.1
SGR-72.5-2A4	73.6	74.5	104.1	7.1
SGR-73.6-2A4	74.6	75.7	104.1	7.1
SGR-74.7-2A4	75.8	76.7	104.1	7.1
SGR-75.7-2A4	76.8	77.7	104.1	7.1
SGR-76.7-2A4	77.8	78.9	104.1	7.1
SGR-77.9-2A4	79.0	79.9	104.1	7.1
SGR-78.9-2A4	80.0	80.9	104.1	7.1

SGR-79.9-2A4	81.0	82.0	104.1	7.1
SGR-81.1-2A4	82.1	83.1	104.1	7.1
SGR-82.1-2A4	83.2	84.1	104.1	7.1
SGR-83.1-2A4	84.2	85.2	104.1	7.1
SGR-84.2-2A4	85.3	86.2	104.1	7.1
SGR-85.2-2A4	86.3	87.2	116.8	7.1
SGR-86.3-2A4	87.3	88.4	116.8	7.1
SGR-87.4-2A4	88.5	89.4	116.8	7.1
SGR-88.4-2A4	89.5	90.4	116.8	7.1
SGR-89.4-2A4	90.5	91.6	116.8	7.1
SGR-90.6-2A4	91.7	92.6	116.8	7.1
SGR-91.6-2A4	92.7	93.6	116.8	7.1
SGR-92.6-2A4	93.7	94.7	116.8	7.1
SGR-93.8-2A4	94.8	95.8	116.8	7.1
SGR-94.8-2A4	95.9	96.8	116.8	7.1
SGR-95.8-2A4	96.9	97.9	116.8	7.1
SGR-96.9-2A4	98.0	98.9	116.8	7.1
SGR-97.9-2A4	99.0	99.9	129.5	7.1
SGR-99.0-2A4	100.0	101.1	129.5	7.1
SGR-100.1-2A4	101.2	102.1	129.5	7.1
SGR-101.1-2A4	102.2	103.1	129.5	7.1
SGR-102.1-2A4	103.2	104.3	129.5	7.1
SGR-103.3-2A4	104.4	105.3	129.5	7.1
SGR-104.3-2A4	105.4	106.3	129.5	7.1
SGR-105.3-2A4	106.4	107.4	129.5	7.1
SGR-106.5-2A4	107.5	108.5	129.5	7.1
SGR-107.5-2A4	108.6	109.5	129.5	7.1
SGR-108.5-2A4	109.6	110.6	129.5	7.1
SGR-109.6-2A4	110.7	111.6	129.5	7.1
SGR-110.6-2A4	111.7	112.6	142.2	7.1
SGR-111.7-2A4	112.7	113.8	142.2	7.1
SGR-112.8-2A4	113.9	114.8	142.2	7.1
SGR-113.8-2A4	114.9	115.8	142.2	7.1
SGR-114.8-2A4	115.9	117.0	142.2	7.1
SGR-116.0-2A4	117.1	118.0	142.2	7.1
SGR-117.0-2A4	118.1	119.0	142.2	7.1
SGR-118.0-2A4	119.1	120.1	142.2	7.1
SGR-119.2-2A4	120.2	121.2	142.2	7.1
SGR-120.2-2A4	121.3	122.2	142.2	7.1
SGR-121.2-2A4	122.3	123.3	142.2	7.1
SGR-122.3-2A4	123.4	124.3	142.2	7.1
SGR-123.3-2A4	124.4	125.3	154.9	7.1
SGR-124.4-2A4	125.4	126.5	154.9	7.1
SGR-125.5-2A4	126.6	127.5	154.9	7.1
SGR-126.5-2A4	127.6	128.5	154.9	7.1
SGR-127.5-2A4	128.6	129.7	154.9	7.1
SGR-128.7-2A4	129.8	130.7	154.9	7.1
SGR-129.7-2A4	130.8	131.7	154.9	7.1
SGR-130.7-2A4	131.8	132.8	154.9	7.1
SGR-131.9-2A4	132.9	133.9	154.9	7.1
SGR-132.9-2A4	134.0	134.9	154.9	7.1
SGR-133.9-2A4	135.0	136.0	154.9	7.1
SGR-135.0-2A4	136.1	137.0	154.9	7.1
SGR-136.0-2A4	137.1	138.0	167.6	7.1
SGR-137.1-2A4	138.1	139.2	167.6	7.1
SGR-138.2-2A4	139.3	140.2	167.6	7.1
SGR-139.2-2A4	140.3	141.2	167.6	7.1
SGR-140.2-2A4	141.3	142.4	167.6	7.1
SGR-141.4-2A4	142.5	143.4	167.6	7.1
SGR-142.4-2A4	143.5	144.4	167.6	7.1
SGR-143.4-2A4	144.5	145.5	167.6	7.1
SGR-144.6-2A4	145.6	146.6	167.6	7.1
SGR-145.6-2A4	146.7	147.6	167.6	7.1
SGR-146.6-2A4	147.7	148.7	167.6	7.1
SGR-147.7-2A4	148.8	149.7	167.6	7.1
SGR-148.7-2A4	149.8	150.7	180.3	7.1
SGR-149.8-2A4	150.8	151.9	180.3	7.1
SGR-150.9-2A4	152.0	152.9	180.3	7.1

All prices are subject to change without notice

- **SPLIT RING - METRIC HARDWARE**
- Lead time: 2 weeks ARO
- Includes mounting brackets and metric hardware

- Standard Terms**
- Visa and Mastercard accepted
 - Invoice terms: Net 30 days from invoice date
 - Shipping terms: Ex-works, Mechanic Falls, ME
 - Standard shipping method is UPS Ground PP&A unless otherwise specified.



31 Winterbrook Road
Mechanic Falls, ME 04256 USA
Tel: 866-738-1857
Fax: 207-998-5143
email: sales@est-aegis.com
www.est-aegis.com