

1

2

3

4

5

6

A

A

B

B

C

C

1.545" ± .03"
(39.24mm ± .76)

8mm Mounting Bolts
(4X)

Fiber Ø = Shaft Ø
-.100" [2.54mm]

ID = Shaft Ø + .500" ± .02"
(12.7mm ± .5)

OD = Shaft Ø + 3.0" ± .02"
(76.2mm ± .5)

Mounting Hole Bolt Circle =
Shaft Ø + 1.500" ± .010"
(38.1mm ± .25)

(1.875" [47.62mm]) Max
Over Mounting Bolts

Patented Technology

THEREIN, ARE THE EXCLUSIVE PROPERTY OF ELECTRO STATIC TECHNOLOGY ISSUED IN STRICT CONFIDENCE AND SHALL NOT WITHOUT CONSENT, BE REPRODUCED, COPIED OR USED FOR ANY PURPOSE WHATSOEVER, EXCEPT BUSINESS WITH E.S.T.

UNLESS OTHERWISE SPECIFIED

DIMENSIONS ARE IN

MILLIMETERS

INCHES

UNTOLERANCED DIMENSIONS

OVER TO TOLERANCE

DATE: 5/26/2010

ENGINEER: J. Richardson



ELECTRO STATIC TECHNOLOGY
AN ITW COMPANY

31 WINTERBROOK ROAD, MECHANIC FALLS, MAINE 04256
PHONE (207)998-5140 FAX (207)998-5143

iPRO 120 Split Ring Assembly

DRAWING NO.

Rev. *A

D iPRO 120 for Shaft Diameters From 12.01" [305.05mm] To 30.00" [762.0mm]

To Be Supplied With 4 M8X1.25X50 SHCS And Lock Washers

Any Additional Mounting Hardware Will Be Application Specific
And Require Additional Engineering.

Contains 6 Rows of Conductive Micro Fibers

To Be Installed In Conjunction With AEGIS Colloidal Silver Coating P/N CS015

1

2

3

4

5

6