

1 2 3 4 5 6

A

A

B

B

C

C

D

D

1.545" ± .03"
(39.24mm ± .76)

8mm Mounting Bolts
(4X)

Fiber Ø = Shaft Ø
-.100" [2.54mm]

ID = Shaft Ø + .500" ± .02"
(12.7mm ± .5)

OD = Shaft Ø + 3.0" ± .02"
(76.2mm ± .5)

Mounting Hole Bolt Circle =
Shaft Ø + 1.500" ± .010"
(38.1mm ± .25)

(1.875" [47.62mm]) Max
Over Mounting Bolts

iPRD For Shaft Diameters Greater Than 15.748" (401mm) To 30" [762.0mm]
To Be Supplied With 4 M8X1.25X50 SHCS And Lock Washers
Any Additional Mounting Hardware Will Be Application Specific
And Require Additional Engineering.
Contains 6 Rows Of Conductive Micro Fibers
To Be Installed In Conjunction With AEGIS® Colloidal Silver Coating P/N CS015

Patented Technology

THESE ARE THE EXCLUSIVE PROPERTY OF ELECTRO STATIC TECHNOLOGY ISSUED IN STRICT CONFIDENCE AND SHALL NOT WITHOUT CONSENT, BE REPRODUCED, COPIED OR USED FOR ANY PURPOSE WHATSOEVER, EXCEPT BUSINESS WITH E.S.T.

| | | |
|----------------------------|-------------------------------------|-----------|
| UNLESS OTHERWISE SPECIFIED | | |
| DIMENSIONS ARE IN | | |
| MILLIMETERS | <input type="checkbox"/> | |
| INCHES | <input checked="" type="checkbox"/> | |
| UNTOLERANCED DIMENSIONS | | |
| OVER | TO | TOLERANCE |
| | | |
| | | |
| DATE: 12/7/2011 | | |
| ENGINEER: J. Richardson | | |

 **ELECTRO STATIC TECHNOLOGY**
AN ITW COMPANY

31 WINTERBROOK ROAD, MECHANIC FALLS, MAINE 04256
PHONE (207)998-5140 FAX (207)998-5143

PRO Robust Split Ring Assembly Rev. B

1 2 3 4 5 6