

SGR OD = $\varnothing 5.080^{+0}_{-0.001}$
 $[129.032^{+0}_{-0.025}]$

$\varnothing 4.435$
 $[112.65]$

$\varnothing 4.231$
 $[107.47]$

Notes:

Bore Diameter Requirement: $5.076^{+.001/-0}$ [128.93+.025/-0]


Material: Aluminum

**Conductive Micro-Fiber To Suit
 4.271 [108.48] to 4.31 [109.47] Shaft Diameters**

Patented Technology US Patent 8,199,453; 8,169,766; 7,193,836

THEREIN, ARE THE EXCLUSIVE PROPERTY OF ELECTRO STATIC TECHNOLOGY ISSUED IN STRICT CONFIDENCE AND SHALL NOT WITHOUT CONSENT, BE REPRODUCED, COPIED OR USED FOR ANY PURPOSE WHATSOEVER, EXCEPT BUSINESS WITH E.S.T.

UNLESS OTHERWISE SPECIFIED
 DIMENSIONS ARE IN:
 inch [mm]



ELECTRO STATIC TECHNOLOGY
 AN ITW COMPANY

UNTOLERANCED DIMENSIONS
 $\pm .010$ [0.254mm]

31 WINTERBROOK ROAD, MECHANIC FALLS, MAINE 04256
 PHONE (207)998-5140 FAX (207)998-5143

AEGIS® SGR No Hardware Press Fit

DATE: 6/26/2013

ENGINEER: A. Gen

PART NUMBER: SGR-107.5-0A6

REV A