

SGR OD = $\varnothing 2.100 \pm .010$
[53.340 \pm 0.25]

$\varnothing 1.435$
[36.45]

$\varnothing 1.231$
[31.27]

.295 MAX
[7.49]

Notes:


Includes EP2400 AEGIS® Conductive Epoxy
Material: Aluminum

Conductive Micro-Fiber To Suit
1.271 [32.28] to 1.31 [33.27] Shaft Diameters

Patented Technology US Patent 8,199,453; 8,169,766; 7,193,836

THEREIN, ARE THE EXCLUSIVE PROPERTY OF ELECTRO STATIC TECHNOLOGY ISSUED IN STRICT CONFIDENCE AND SHALL NOT WITHOUT CONSENT, BE REPRODUCED, COPIED OR USED FOR ANY PURPOSE WHATSOEVER, EXCEPT BUSINESS WITH E.S.T.

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN:
inch [mm]



ELECTRO STATIC TECHNOLOGY
AN ITW COMPANY

UNTOLERANCED DIMENSIONS
 $\pm .010$ [0.254mm]

31 WINTERBROOK ROAD, MECHANIC FALLS, MAINE 04256
PHONE (207)998-5140 FAX (207)998-5143

DATE: 3/5/2020

AEGIS® SGR No Hardware Epoxy Mount

ENGINEER: A. Gen

PART NUMBER: SGR-31.3-0AW

REV A