

SGR OD =  $\varnothing 2.680 \pm .010$   
[68.072  $\pm$  0.25]

$\varnothing 1.560$   
[39.62]

$\varnothing 1.356$   
[34.44]

Bolt Circle =  $\varnothing 2.433 \pm .010$   
[61.80  $\pm$  0.25]

$\varnothing .140 \begin{smallmatrix} +.010 \\ -0 \end{smallmatrix}$  THRU  
[ $\varnothing 3.56 \begin{smallmatrix} +0.254 \\ -0 \end{smallmatrix}$  THRU]

.295 MAX  
[7.49]

**Notes:**

Supplied with:  
2, M3 X 0.5 x 14MM SHCS With Appropriate Lock Washers

**Conductive Micro-Fiber To Suit  
1.396 [35.46] to 1.435 [36.45] Shaft Diameters**

Patented Technology US Patent 8,199,453; 8,169,766; 7,193,836


THEREIN, ARE THE EXCLUSIVE PROPERTY OF ELECTRO STATIC TECHNOLOGY ISSUED IN STRICT CONFIDENCE AND SHALL NOT WITHOUT CONSENT, BE REPRODUCED, COPIED OR USED FOR ANY PURPOSE WHATSOEVER, EXCEPT BUSINESS WITH E.S.T.

UNLESS OTHERWISE SPECIFIED  
DIMENSIONS ARE IN:  
inch [mm]

UNTOLERANCED DIMENSIONS  
 $\pm .010$  [0.254mm]

DATE: 3/12/2020

ENGINEER: A. Gen



ELECTRO STATIC TECHNOLOGY  
AN ITW COMPANY

31 WINTERBROOK ROAD, MECHANIC FALLS, MAINE 04256  
PHONE (207)998-5140 FAX (207)998-5143

AEGIS® SGR SHCS Bolt Thru

PART NUMBER: SGR-34.4-3

REV E