

SGR OD =  $\varnothing 2.680 \pm .010$   
 [68.072  $\pm$  0.254]

$\varnothing 1.810$   
 [45.97]

$\varnothing 1.646$   
 [41.81]

.295 MAX  
 [7.49]

**Notes:**


**Includes EP2400 AEGIS® Conductive Epoxy**  
**Material: Aluminum**

**Conductive Micro-Fiber To Suit**  
**1.686 [42.82] to 1.73 [43.94] Shaft Diameters**

Patented Technology US Patent 8,199,453; 8,169,766; 7,193,836

THEREIN, ARE THE EXCLUSIVE PROPERTY OF ELECTRO STATIC TECHNOLOGY ISSUED IN STRICT CONFIDENCE AND SHALL NOT WITHOUT CONSENT, BE REPRODUCED, COPIED OR USED FOR ANY PURPOSE WHATSOEVER, EXCEPT BUSINESS WITH E.S.T.

UNLESS OTHERWISE SPECIFIED  
 DIMENSIONS ARE IN:  
 inch [mm]



**ELECTRO STATIC TECHNOLOGY**  
 AN ITW COMPANY

UNTOLERANCED DIMENSIONS  
 $\pm .010$  [0.254mm]

31 WINTERBROOK ROAD, MECHANIC FALLS, MAINE 04256  
 PHONE (207)998-5140 FAX (207)998-5143

DATE: 7/14/2015

AEGIS® SGR No Hardware Epoxy Mount

ENGINEER: A. Gen

PART NUMBER: SGR-41.8-0AW

REV A