

.295 MAX
[7.49]

SGR OD = $\varnothing 3.080^{+0}_{-.001}$
[78.232⁺⁰_{-0.03}]

$\varnothing 2.185$
[55.50]

$\varnothing 2.066$
[52.48]

Notes:

Bore Diameter Requirement: 3.076 +.001/-0 [78.13+.025/-0]

Material: Aluminum

Conductive Micro-Fiber To Suit
2.106 [53.49] to 2.145 [54.48] Shaft Diameters

Patented Technology US Patent 8,199,453; 8,169,766; 7,193,836


THEREIN, ARE THE EXCLUSIVE PROPERTY OF ELECTRO STATIC TECHNOLOGY ISSUED IN STRICT CONFIDENCE AND SHALL NOT WITHOUT CONSENT, BE REPRODUCED, COPIED OR USED FOR ANY PURPOSE WHATSOEVER, EXCEPT BUSINESS WITH E.S.T.

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN:
inch [mm]

UNTOLERANCED DIMENSIONS
 $\pm .010$ [0.254mm]

DATE: 3/4/2020

ENGINEER: A. Gen



ELECTRO STATIC TECHNOLOGY
AN ITW COMPANY

31 WINTERBROOK ROAD, MECHANIC FALLS, MAINE 04256
PHONE (207)998-5140 FAX (207)998-5143

AEGIS® SGR No Hardware Press Fit

PART NUMBER: SGR-52.5-0A6

REV A